


ROUTING PROTOCOL BASICS

Let's spice things up....




A much more complex topology...

Routing Protocols

- Larger network topologies can't rely on static routing configuration
 - Big topologies
 - What's the best path?
 - Reconfiguration?
- Routing protocols define the procedures and the messages to exchange routing information between the routers and automatically construct the routing tables
- Routing protocols make use of **graph search algorithms** to compute “the best paths” between all possible destinations
 - Dijkstra, Bellman-Ford
- Network topologies can be modeled as weighted oriented graphs (router, networks → **nodes**; links → **edges**; weights → **link metrics**)
- Construction of the routing tables is equivalent to find all the “best” paths between all nodes of the graph
 - “Best” is not always equal to “shortest”
- Let's take a look at a simple example of Dijkstra


Dijkstra algorithm at a glance



- The algorithm is iterative:
 - At the K^{th} step we have K nodes that can be reached from the source node S with the shortest path
 - Such K nodes are in the set $T = \{V_1, V_2, \dots, V_m\}$
 - At step $(K+1)^{\text{th}}$ add the node with the path with minimum weight from S that transit in the node in T
 - The algorithm ends when all nodes have been explored
- The weight of a path is the sum of the weights (costs) of all the edge forming the path

Dijkstra: a simple example


Step 1



$$T_1 = \{1\}$$


Dijkstra: a simple example

Step 1



$$T_1 = \{1\}$$


Step 2



$$T_2 = \{1, 4\}$$


Dijkstra: a simple example

Step 1




$$T_1 = \{1\}$$

Step 2



$$T_2 = \{1, 4\}$$


Step 3



$$T_3 = \{1, 2, 4\}$$

Dijkstra: a simple example


Step 4



$$T_4 = \{1, 2, 4, 5\}$$


Dijkstra: a simple example

Step 4



$$T_4 = \{1, 2, 4, 5\}$$


Step 5



$$T_5 = \{1, 2, 3, 4, 5\}$$


Dijkstra: a simple example

Step 4




$$T_4 = \{1, 2, 4, 5\}$$

Step 5



$$T_5 = \{1, 2, 3, 4, 5\}$$

Step 6



$$T_6 = \{1, 2, 3, 4, 5, 6\}$$

How can Dijkstra be used in a routing protocol?

- There are different routing protocols that use Dijkstra as search graph algorithm to construct the routing tables
- All the routers exchange information about all the respective neighbor routers and the relative links to them (neighbor routers = routers at 1 hop)
- After a “convergence time” all the routers know the complete topology
- Each router constructs the graph representing the network topology and then run Dijkstra with themselves as source node
- Such a routing protocol is called: Link State protocol
 - Because every node in the network has to know the entire topology (i.e.: the state of each link in the network topology)

OSPF

- **Open Shortest Path First** is a link state routing protocol that uses Dijkstra to construct the routing tables
- Each router advertises its identity to the neighbors
- Each router transmits a Link State Packet (LSP) containing the list of the links and their costs
- A LSP is transmitted to all the other routers (**flooding mechanism**)
- All the routers can locally build the entire network topology by gathering all the received LSPs


Distance Vector protocols

- A distance vector routing protocol is a protocol in which all the routers know only the routing tables of their neighbors (the vectors of the distance to all possible destinations)
- The next hop to the other destinations is picked up by choosing the minimizing

$$\text{Cost}(i, d) = (L_i + C_{d,i})$$

- Where:
 - i is the next hop
 - L_i is the cost of the link to i
 - d the destination
 - $C_{d,i}$ is the cost of the route to d in the routing table of i

Routing Protocol classification



NOTE: Too many things about routing protocols have been ignored. We don't want to understand the routing protocols in details, we just wanted an introduction to understand what we are going to see in the following slides...

QUAGGA

- Quagga is an opensource routing software suite, providing implementations of OSPFv2, OSPFv3, RIP v1 and v2, RIPng and BGP-4 for Unix platforms, particularly FreeBSD, Linux, Solaris and NetBSD
- Quagga is a fork of GNU Zebra for which development was abandoned in 2003
- The Quagga architecture consists of a core daemon (zebra) that presents the Zserv API over a Unix or TCP stream to Quagga daemons:
 - `ospfd` for OSPFv2
 - `ripd` for RIPv1 and RIPv2
 - `ospf6d` for OSPFv3 (IPv6)
 - `ripngd` for RIPng (IPv6)
 - `bgpd` for BGPv4+
 - `isisd` for IS-IS
- The zebra daemon is responsible for providing an interface to the kernel IP and routing subsystems
- The per-protocol daemon are responsible for performing all protocol-specific operations as described in the relevant RFCs
- Each daemon has its own configuration file and terminal interface which can be accessed by telnet
- The `vttysh` tool is provided to configure the Quagga router from the localhost, in a unique interface

QUAGGA configuration

- Activate the daemon by putting “yes” for the protocol you need in the file `/etc/quagga/daemons`
 - For example: `zebra=yes; ospfd=yes`
 - Each daemon has its own configuration file
 - `bgpd.conf, ospfd.conf, ripd.conf, etc..`
- By default, the quagga daemons are listening only to the loopback interface `127.0.0.1`. If you want to telnet a quagga daemon remotely you can, in the `/etc/quagga/debian.conf` file
 - Either indicate one or several IP addresses or remove the `-A` option meaning that you can telnet a daemon on any of its IP addresses
 - Examples:

```
ospfd_options=" --daemon -A 127.0.0.1 192.168.1.104"  
zebra_options=" --daemon"
```
- To enable vtysh put in `/etc/quagga/debian.conf`
 - `vtysh_enable=yes`

QUAGGA daemons shells

- you can access the daemons by telnetting their port number because each daemon has its own configuration file and terminal interface
- The daemon name/port binding is stored in `/etc/services`, so you can also use the name
 - `telnet localhost ripd`
 - `telnet localhost 2008`

Anyway, as it's not very practical to configure your router by telnetting its daemons separately, `vttysh` has been created to configure everything in one single interface

To connect just type:

```
vttysh
```

zebra	2601
ripd	2602
ripng	2603
ospfd	2604
bgpd	2605
ospf6d	2606
isisd	2008

QUAGGA - configuration files

- Official docs
 - <http://www.nongnu.org/quagga/docs>
- From vtysh you can configure everything (interfaces, ip configuration, routing protocols parameters, etc..) and dump the status of your router (show routes, show interfaces, etc..)
- We are not gonna learn how to use the vtysh console, but we'll try to configure the quagga daemons via configuration files
- BTW, the configuration lines are exactly like the commands you type from the shells

Simple configuration examples

```
! *- zebra *-
hostname router2
password zebra
enable password zebra

interface eth0
ip address 10.2.0.1/16
link-detect
bandwidth 100000

interface eth1
ip address 10.0.0.2/16
link-detect
bandwidth 100000

interface eth2
ip address 10.3.0.1/16
link-detect
bandwidth 5000
```

zebra.conf

```
hostname router2
password zebra
log file /var/log/quagga/ospfd.log

interface eth0
ospf hello-interval 2

interface eth1
ospf hello-interval 2


interface eth2
ospf hello-interval 2

router ospf
network 10.0.0.0/16 area 0.0.0.0
network 10.2.0.0/16 area 0.0.0.0
network 10.3.0.0/16 area 0.0.0.0
```

ospfd.conf

Lab3-quagga

pcs{1-4} in the lab get the .100 address of their respective subnets



Default bandwidth = 100Mbit/s
Router3 ↔ Router6 link: 40 Kbit/s

Lab3-quagga

```
router3
<none>
.....
— Netkit phase 2 initialization terminated —

router3 login: root (automatic login)
router3:~# ip r
10.2.0.0/16 dev eth1 proto kernel scope link src 10.2.0.2
10.4.0.0/16 dev eth0 proto kernel scope link src 10.4.0.1
10.9.0.0/16 dev eth2 proto kernel scope link src 10.9.0.2
router3:~# ip r
10.2.0.0/16 dev eth1 proto kernel scope link src 10.2.0.2
10.3.0.0/16 via 10.2.0.1 dev eth1 proto zebra metric 20
10.0.0.0/16 via 10.2.0.1 dev eth1 proto zebra metric 20
10.1.0.0/16 via 10.2.0.1 dev eth1 proto zebra metric 30
10.6.0.0/16 via 10.2.0.1 dev eth1 proto zebra metric 50
10.7.0.0/16 via 10.2.0.1 dev eth1 proto zebra metric 30
10.4.0.0/16 dev eth0 proto kernel scope link src 10.4.0.1
10.5.0.0/16 via 10.2.0.1 dev eth1 proto zebra metric 40
10.8.0.0/16 via 10.2.0.1 dev eth1 proto zebra metric 40
10.9.0.0/16 dev eth2 proto kernel scope link src 10.9.0.2
router3:~#
```

Intuitively, for router3 the next hop to 10.5.0.0/16 is router2 (3 hops) and not router6 (2 hops)....

Lab3-quagga

```
pc3
Lab directory (host): /home/marlon/Labs/Lab3-quagga
Version: <none>
Author: <none>
Email: <none>
Web: <none>
Description:
<none>


#####

— Netkit phase 2 initialization terminated —

pc3 login: root (automatic login)
pc3:~# traceroute 10.10.0.100
traceroute to 10.10.0.100 (10.10.0.100), 64 hops max, 40 byte packets
 1 10.4.0.1 (10.4.0.1)  5 ms  0 ms  0 ms
 2 10.2.0.1 (10.2.0.1) 10 ms  0 ms  0 ms
 3 10.0.0.1 (10.0.0.1)  2 ms  0 ms  0 ms
 4 10.1.0.2 (10.1.0.2)  0 ms  0 ms  0 ms
 5 10.5.0.3 (10.5.0.3)  0 ms  0 ms  0 ms
 6 10.10.0.100 (10.10.0.100) 37 ms  0 ms  0 ms
pc3:~#
```

...and, clearly, pc3 → pc4 path is: router3 → router2 → router1 → router4 → router8

Exercise




Exercise (cont.d)

- Let's do it together starting from Lab3-quagga
- Add router9
- Enable ospfd daemon
- Change file permission as needed
- Configure zebra
- Configure ospfd
- Start quagga

Propagate default routes with OSPF

- Let's say a router has a default GW toward internet.. How do I advertise this?
- Use `default-information` directive
- Originate an AS-External (type-5) LSA describing a default route into all external-routing capable areas
- Type 5 - External LSA - these LSAs contain information imported into OSPF from other routing processes. They are flooded to all areas unchanged

Add internet access via TAP iface



Propagate default gw

- Preliminary
 - Add in lab.conf:

```
router5[2]=tap,192.168.25.1, 192.168.25.2
```
 - Add in router5.startup (for masquerading and make all subnets access the Internet)

```
iptables -t nat -A POSTROUTING -j MASQUERADE
```
- A default GW is automatically installed in router5 rtable by simply adding a TAP interface
- To propagate this route unchanged to all areas:
 - Add in router5/etc/quagga/ospfd.conf

```
default-information originate always
```

Let's test it....

```
pc1:~# ping 8.8.8.8
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data:
64 bytes from 8.8.8.8: icmp_seq=1 ttl=53 time=239 ms
64 bytes from 8.8.8.8: icmp_seq=2 ttl=53 time=117 ms
64 bytes from 8.8.8.8: icmp_seq=3 ttl=53 time=209 ms
^C
--- 8.8.8.8 ping statistics ---
4 packets transmitted, 3 received, 25% packet loss, time 3028ms
rtt min/avg/max/mdev = 117.862/189.143/239.962/51.905 ms
pc1:~#

router7:~# ip r
10.2.0.0/16 via 10.7.0.1 dev eth0 proto zebra metric 30
10.3.0.0/16 via 10.7.0.1 dev eth0 proto zebra metric 30
10.0.0.0/16 via 10.7.0.1 dev eth0 proto zebra metric 20
10.1.0.0/16 via 10.7.0.1 dev eth0 proto zebra metric 20
10.6.0.0/16 via 10.7.0.1 dev eth0 proto zebra metric 40
10.7.0.0/16 dev eth0 proto kernel scope link src 10.7.0.2
10.4.0.0/16 via 10.7.0.1 dev eth0 proto zebra metric 40
10.5.0.0/16 via 10.7.0.1 dev eth0 proto zebra metric 30
10.10.0.0/16 via 10.7.0.1 dev eth0 proto zebra metric 40
10.8.0.0/16 dev eth1 proto kernel scope link src 10.8.0.1
10.9.0.0/16 via 10.7.0.1 dev eth0 proto zebra metric 2530
default via 10.7.0.1 dev eth0 proto zebra metric 1
router7:~#

router1:~# ip r
4: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 4a:99:eb:8c:6f:d4 brd ff:ff:ff:ff:ff:ff
    inet 10.1.0.1/16 brd 10.1.255.255 scope global eth1
    inet6 fe80::4899:ebff:fe8c:6fd4/64 scope link
        valid_lft forever preferred_lft forever
5: eth2: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 7a:a9:5d:95:f5:6f brd ff:ff:ff:ff:ff:ff
    inet 10.7.0.1/16 brd 10.7.255.255 scope global eth2
    inet6 fe80::78a9:5dff:fe95:f56f/64 scope link
        valid_lft forever preferred_lft forever
router1:~# ip r
10.2.0.0/16 via 10.0.0.2 dev eth0 proto zebra metric 20
10.3.0.0/16 via 10.0.0.2 dev eth0 proto zebra metric 20
10.0.0.0/16 dev eth0 proto kernel scope link src 10.0.0.1
10.1.0.0/16 dev eth1 proto kernel scope link src 10.1.0.1
10.6.0.0/16 via 10.1.0.2 dev eth1 proto zebra metric 30
10.7.0.0/16 dev eth2 proto kernel scope link src 10.7.0.1
10.4.0.0/16 via 10.0.0.2 dev eth0 proto zebra metric 30
10.5.0.0/16 via 10.1.0.2 dev eth1 proto zebra metric 20
10.10.0.0/16 via 10.1.0.2 dev eth1 proto zebra metric 30
10.8.0.0/16 via 10.7.0.2 dev eth2 proto zebra metric 20
10.9.0.0/16 via 10.0.0.2 dev eth0 proto zebra metric 2520
default via 10.1.0.2 dev eth1 proto zebra metric 1
router1:~#

router4:~# ip r
<none>
-----
----- Netkit phase 2 initialization terminated -----
prova ciao ciao 2014
router4 login: root (automatic login)
Last login: Fri Mar 28 11:56:16 UTC 2014 on tty1
router4:~# ip r
10.2.0.0/16 via 10.1.0.1 dev eth0 proto zebra metric 30
10.3.0.0/16 via 10.1.0.1 dev eth0 proto zebra metric 30
10.0.0.0/16 via 10.1.0.1 dev eth0 proto zebra metric 20
10.1.0.0/16 dev eth0 proto kernel scope link src 10.1.0.2
10.6.0.0/16 via 10.5.0.2 dev eth1 proto zebra metric 20
10.7.0.0/16 via 10.1.0.1 dev eth0 proto zebra metric 20
10.4.0.0/16 via 10.1.0.1 dev eth0 proto zebra metric 40
10.5.0.0/16 dev eth1 proto kernel scope link src 10.5.0.1
10.10.0.0/16 via 10.5.0.3 dev eth1 proto zebra metric 20
10.8.0.0/16 via 10.1.0.1 dev eth0 proto zebra metric 30
10.9.0.0/16 via 10.5.0.2 dev eth1 proto zebra metric 2520
default via 10.5.0.2 dev eth1 proto zebra metric 1
router4:~#
```

to router5